

MVHB-220 series

HAND LEVER VALVE



Specification

Model	MVHB-220-4TV MVHB-220-4TV-SP	MVHB-220-4TV* MVHB-220-4TV*-SP
Bore No. (Port size)	8A (1/4)	
No. of port	5	
No. of position	2	3
Medium	Air	
Operating pressure range	0~0.8 MPa	
Effective orifice	18 mm ²	16 mm ²
Ambient temperature	-5~+60°C (No freezing)	
Weight	193 g	234 g

Order example

MVHB - 220 - 4TVC - SP - M - □ - G

MODEL

BODY WIDTH

4: 4way (5 port)

VALVE TYPE

Blank: 5/2
C: Closed center (5/3)
P: Pressure center(5/3)
R: Exhaust center (5/3)

SPRING RETURN


*1,2
DUST COVER MATERIAL
Blank: NBR
E: EPDM

Blank: Standard type
M: Panel mounting

PORT THREAD

Blank: Rc thread
G: G thread
NPT: NPT thread

Panel mounting style



*1. NBR: Good oil resistance and abrasion resistance, not suitable for using in polar solvents.

EPDM: Excellent water resistance and chemical resistance, not suitable for using oil place.

*2. Suitability of material please refer to page 2-3~5.

